

olume XXII

APPRAISAL BULLETIN

PUBLISHED IN THE INTERESTS OF REAL ESTATE ANALYST SUBSCRIBERS BY

ROY WENZLICK & CO.

Real Estate Economists, Appraisers and Counselors

SEPTEMBER 25 1953

Number 41

Copyright 1953-by ROY WENZLICK & CO. -Swint Louis
REAL ESTATE ECONOMISTS, APPRAISERS AND COUNSELORS

CONSTRUCTION COSTS OF CHURCHES

N the following pages of this bulletin are charts and tables showing the cubic foot cost of three types of churches - frame, masonry with frame interior, and fireproof. These are the same three buildings for which we ran costs in February of 1949. As we pointed out at that time, the original cost is known for each of these buildings, and the figures shown have been brought forward from that point on a carefully computed index.

Churches, as a general rule, are very difficult to appraise. They present most of the problems common to special use properties and can usually be appraised only by the replacement cost method. The income approach is useless, and the comparative method is seldom feasible because churches differ so widely in size, shape, and quality of construction. Fortunately, most church appraisals are made for insurance purposes and not for determining market value. Most of the requests we receive for church cost information come from clients who are members of either the financial or building committees of their churches. In the first instance, the problem is one of insurance, and in the second, the construction of a new church or of an addition to the present edifice. The specifications for the three buildings follow:

FIREPROOF CHURCH: concrete foundations; partial basement; exterior walls, face brick with stone trim; stained glass windows; roof, slate over steel truss; copper flashing and gutters; floors, tile and hardwood over claytile filled concrete; partitions plaster over tile, or metal lath; ceilings, suspended plaster; birch doors and trim; vacuum steam heating; steel boiler; good grade of modern plumbing facilities.

MASONRY CHURCH WITH FRAME INTERIOR: concrete foundations; partial basement; exterior walls, stone; stained glass windows; roof, slate; copper flashing and gutters; hardwood and linoleum floors; trim and doors, birch and oak; partitions, stud, metal lath and plaster; ceilings plastered; steam heating with steel boiler; modern plumbing facilities of fair grade.

FRAME CHURCH: concrete foundation, partial basement; walls, drop siding and sheathing over studs; roof, slate; copper flashing and gutters; steam heating with steel boiler; hardwood floors; partitions, stud, wood lath and plaster; ceiling in auditorium exposed beam and sheathing; other rooms have plastered ceilings; pine trim and doors; modern plumbing facilities of fair grade. (Organ and kitchen equipment are not included in any of the costs.)





